

RUG HUGGER™/QUILT KEEPER™ INSTALLATION INSTRUCTIONS

INSERTING TEXTILE INTO HANGER:

Your textile should be inserted into the Rug Hugger™ before hanging on the wall in the following manner:

- Place backboard top side up on a flat surface.
- Place the edge of your textile on top of the backboard just up to the holes. Be careful that none of the fabric is extending over holes.
- Place the top board over the textile with the smaller lip on the backside of the top board pointing down. Position the top board so the holes are lined up with the holes on the backboard.
- Place the wooden screws in the holes and turn until the textile is secured. Again, be careful not to catch the fabric in the holes.
- There are keyhole slots routed into the backside of the backboard. Hang your Rug Hugger by slipping these slots over nails or screws that have been inserted into the wall. The keyhole slots are placed at 16" on center intervals should you wish to secure the hanger to your wall studs. If you have drywall construction and will not be placing your screws into the studs, plastic anchors may be inserted into the wall first to give the screws extra strength. These anchors can be purchased at a hardware store.

SUGGESTIONS FOR DISPLAY:

Choose a location to display your textile that is protected from direct sunlight. The sun's ultraviolet rays will fade the colors and destroy the fabric of your textile. When hanging a loosely woven textile with a pattern that can hang in any direction, rotate your hanging periodically from end to end. Gravity may cause some stretching, and this will prevent your textile from stretching irregularly.